

SVP-HP™ Grade Hydrogen Peroxide (H₂O₂), 50% and 70%

SVP-HP™ Grade Hydrogen Peroxide (H₂O₂), 50% and 70% Technical Data Sheet

Introduction

Solvay Chemicals, Inc. manufactures an approved version of Eka Chemicals' SVP-HP™⁽¹⁾ hydrogen peroxide. SVP-HP™ is specifically formulated as a reducing agent in Eka Chemicals' SVP-HP™ and HP-A™ chlorine dioxide generators. It contains a proprietary additive package that enhances the performance of the generator, and corrosion inhibitors that make it suitable for storage in both stainless steel and high-purity aluminum storage tanks.

Applications

SVP-HP™ hydrogen peroxide is specifically formulated for use as a reducing agent in Eka Chemicals' chlorine dioxide generators, however; it is also suitable for use in almost any application where a non-tin stabilized hydrogen peroxide product is required.

Availability

SVP-HP™ hydrogen peroxide is sold in 50% and 70% concentrations and is available in bulk truck or railcar quantities from Solvay Chemicals' Deer Park, Texas and Longview, Washington plants. For more information, or to place an order, please contact Solvay Chemicals at 1-800-SOLVAY-C, 800-765-8292 or 713-525-6500.

Physical Properties

Hydrogen peroxide is a clear and colorless liquid. It is slightly denser than water, but is miscible with water in all proportions. Hydrogen peroxide decomposes exothermally to water and oxygen with no toxic residues. The decomposition is normally slow (< 1% / year) with no temperature rise but is accelerated by heat and decomposition catalysts such as transition metals and their compounds, strong acids, and strong alkalis.

Typical Analysis	50% SVP-HP™ Grade	70% SVP-HP™ Grade
Concentration in water, % w/w	50.0 - 51.0	70.0 - 71.0
Apparent pH	1.0 - 2.0	-0.5 - 0.5
Appearance	Clear, colorless liquid	Clear, colorless liquid

⁽¹⁾SVP-HP is a trademark of Eka Chemicals.



Solvay
Chemicals



Interox, Fluorides & Minerals

SVP-HP™ Grade Hydrogen Peroxide (H₂O₂), 50% and 70% Technical Data Sheet

Storage and Handling

- Store hydrogen peroxide in the original vented container, upright, in a cool, ventilated area where it is protected from damage, or in bulk storage tanks made from approved alloys of stainless steel and aluminum.
- Do not store other chemicals, fuels, or combustible materials near hydrogen peroxide.
- Never return unused hydrogen peroxide to the storage container.
- When empty, rinse all peroxide containers thoroughly with clean water before discarding.
- Use only approved material for pumps, piping, and hoses.

Safety

- Persons working with hydrogen peroxide should be familiar with personal protective equipment, first aid measures and the proper safety and handling procedures. Consult the Material Safety Data Sheet (MSDS) for appropriate information.
- Prevent accidental decomposition by keeping the product free of contaminants.
- Prevent fires by avoiding accidental spills. Water is the preferred method for extinguishing fires in which hydrogen peroxide is present.
- Spills and leaks should be contained, diluted with copious amounts of water and disposed of in compliance with local regulations.
- Hydrogen peroxide storage or handling areas should be equipped with a safety shower, an eyewash station, and a water hose.

First Aid

In case of product splashing into the eyes and face, treat eyes first.

- **Eye contact:** Flush eyes immediately with water for at least 15 minutes. Call a physician.
- **Skin contact:** Immediately flush skin with water while removing contaminated clothing and shoes. Call a physician if irritation persists.
- **Inhalation:** Remove the victim from the contaminated area to fresh air. Call a physician in case of respiratory symptoms.
- **Ingestion:** Consult with a physician immediately in all cases. DO NOT induce vomiting. If victim is conscious, rinse mouth and give fresh water.

Danger: Hydrogen Peroxide solutions are strong oxidizers and corrosive to the eyes, mucous membranes and skin. Consult the MSDS for the appropriate Personal Protective Equipment to wear when handling hydrogen peroxide. In case of contact with the eyes, skin or clothing, flush with large amounts of water for 15 minutes. In case of ingestion, sit upright, drink large quantities of water to dilute the stomach contents and seek immediate medical attention. Product in contact with combustible materials may cause fires.

SVP-HP™ Grade Hydrogen Peroxide (H₂O₂), 50% and 70%

SVP-HP™ Grade Hydrogen Peroxide (H₂O₂), 50% and 70% Technical Data Sheet

Before using, read Material Safety Data Sheet (MSDS) for this chemical.

Solvay Chemicals, Inc.

24 hour Emergency Phone Number - 800-424-9300 (CHEMTREC®)

To our actual knowledge, the information contained herein is accurate as of the date of this document. However, neither Solvay Chemicals, Inc. nor any of its affiliates makes any warranty, express or implied, or accepts any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use, the manner of use and whether any patents are infringed.